



DATENBLATT | datasheet

Stationäres Lesegerät | Stationary Reader

ARE K1

Elektrische Daten | electrical characteristics

Lesesystem reading systems	TROVAN, PSK
Betriebsfrequenz operational frequency	128 kHz
Schnittstelle interface	RS 232, Profibus DP bis up to 12 Mbit/s
Software software	Einfaches serielles ASCII Protokoll Easy serial ASCII based protocol
Stromversorgung power supply	24V
Optionen options	2 digitale Ausgänge 2 digital outputs
Externa Antenne external antenna	Geeignet für suitable for : AAN -FK2, -FK6

Umweltbedingungen | environment

Lagertemperatur storage temperature	-20°C bis up to +70°C
Betriebstemperatur operating temperature	-20°C bis up to +70°C
Gehäuse Schutzklasse packaging protection class	IP 65
Schock&Vibration Shock&Vibration	IEC 68-2-6 / 29

Abmessungen | dimension

Gewicht weight	Ca. 1800 g
Länge length	220 mm
Breite width	122 mm
Höhe height	80 mm
Material material	Aluminium Spritzguss Aluminium Die Cast



AEG Identifikationssysteme GmbH

Hörvelsinger Weg 47, D-89081 Ulm | P: +49 (0)731 140088-0 | F: +49 (0)731 140088-9000

E-Mail: info@aegid.de | www.aegid.de

AEG is a registered trademark used under license from AB Electrolux (publ).